

ZEN

Aplique led
Led Wall lamp

Instalación:

- *Superficie*

Installation:


- *Surface*



Aplique de superficie de LED, de luz directa e indirecta, ideal para su instalación en hoteles, casas rurales...

Surface LED wall light, direct and indirect light, ideal for installation in hotels, cottages ...

Referencia <i>Reference</i>	Potencia <i>Power</i>	Voltaje <i>Voltage</i>	Frecuencia <i>Frequency</i>	FP <i>PF</i>	Ra <i>Ra</i>	THD <i>THD</i>	Estanqueidad <i>Protection</i>
ZEN20	20 W	AC 110 - 240V	50 / 60 Hz	> 0,9	>90	< 20%	IP 40



Características:

- Aplique de superficie de led
- Cuerpo realizado en chapa de acero fosfatado y pintado con resina epoxi poliéster termo-endurecida de color blanco.
- Reflector aluminio, con cierre en color negro
- Equipo lumínico y driver incluido.
- Vida útil media: L70B50 40.000 horas
- UGR < 19
- Ra >90
- Temperatura de trabajo: -20° C- +40°C

Características:

- Wall surface led
- Body made of phosphatized steel sheet and painted with white thermo-hardened polyester epoxy resin.
- Aluminum reflector, with black closure
- Lighting equipment and driver included.
- Average lifespan: L70B50 40,000 hours
- UGR <19
- Ra > 90
- Working temperature: -20° C- + 40°C

Accesorios opcionales:

- Balasto electrónico regulable

Optional accessories:

- Dimmable electronic ballast

Datos lumínicos:

Light data:

	ZEN10	
	LED	Luminaria
3000 K	1.650 lm	1.450 lm

